Material Safety Data Sheet



MSDS No. : 3030E Revision : 3

Prepared Date : December 12, 2012

1. Product and company identification

Product name YMC-BioPro (Packings)

Manufacturer YMC Co., Ltd Quality Assurance Dept.

5-28, Kokufudai, Komatsu, Ishikawa 923-8557, Japan

TEL: +81-761-47-8224 FAX: +81-761-47-8019

Material Uses Research & Development, Industry use

2. Hazards identification

GHS Classification Flammable liquid - Category 3

Eye damage/Eye Irritation - Category 2 Germ cell mutagenicity - Category 1 Reproductive toxicity - Category 1

Specific target organ toxicity (Repeated exposure) - Category 1(Liver), Category 2(Peripheral nervous system)

Hazard symbol







Warning!

Emergency overview Flammable liquid and vapor.

Causes serious eye irritation. May cause genetic effects.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure. (Liver)

May cause damage to organs through prolonged or repeated exposure. (Peripheral nervous system)

Remarks < Personal precaution>

Avoid exposure - obtain and understand special instructions before use. Keep away from heat, sparks and open flame. Wear appropriate protective equipment such as gloves, safety glasses, lab coat. Avoid prolonged contact with skin and breathing of vapor or spray mist. Do not eat, drink or smoke before handling the product. Wash hands thoroughly after handling the product.

<First-aid>

EYE CONTACT: Immediately flush eyes with plenty of water for at least 10 minutes, lifting the lids occasionally. Check for and remove contact lenses, if possible./SKIN CONTACT: Remove contaminated clothing and shoes. Wash with plenty of water.

/EXPOSURE OR POSSIBLE EXPOSURE: Seek medical attention.

<Storage>

Store and lock in a cool, dry, well-ventilated area.

<Disposal>

Dispose of the product and containers via a licensed waste disposal contractor.

Other toxicity Not applicable.

3. Composition/Information on ingredients

Chemical Name Hydrophilic acrylic polymers (20% Ethanol suspension)

Ingredient Chemical Name Chemical Formula % by weight CAS No Hydrophilic acrylic polymers N/A 15-20 N/A

(Ethyl alcohol)

Ethanol

Purified water H_2O 65-70 N/A

C₂H₅OH

N/A; Not Applicable or Not Available

10-15

64-17-5

4. First-aid measures

INHALATION Remove victim to fresh air and lay in position to secure breathing. Seek medical attention immediately.

EYE CONTACT Immediately flush eyes with plenty of water for at least 10 minutes, lifting the lids occasionally. Check for and remove contact

lenses, if possible. Seek medical attention immediately.

SKIN CONTACT INGESTION

Flush thoroughly with a large amount of water. Immediately remove contaminated clothing. Seek medical attention if needed. Wash mouth with plenty of water. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight

Wear appropriate protective equipment such as gloves, safety glasses, etc. when administering first aid.

clothing such as a collar, tie, belt or waistband. Seek medical attention immediately.

Notes to Physician None

5. Fire-fighting measures

First Aid Instructions

Extinguishing media

Dry chemical, carbon dioxide, foam, or sand. Water spray to cool fire-exposed containers.

Extinguishing media

to be avoided

Water jet.

Unusual hazards Special fire-fighting

procedures

None known Keep personnel removed and upwind of any fire and isolate the area. Cool surrounded area with water spray to prevent increasing

temperature of equipment and containers. Take appropriate measures to avoid discharging the effluent into the environment. Fire-fighters should battle the fire from upwind. Fire-fighters should wear appropriate protective equipment such as heat resistant

gloves and full face piece, positive pressure, self-contained breathing apparatus (SCBA).

Accidental release measures

Protection of fire-fighters

Personal precaution / Personal protective

equipment and Emergency

measures.

Evacuate and isolate the area. Keep unnecessary and unprotected personnel from entering.

Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Wear protective equipment such as rubber gloves and boots, protective goggles, full protective suit when handling spilled material. Remove all sources of ignition such as sparks, flames, heat, etc and provide adequate ventilation. Avoid breathing vapor or mist.

Avoid dispersal of spilled material and runoff into the soil, waterways and drains. Environmental precautions

Method of containment

and cleanup

Stop discharge. Transport containers from the area after confirming their safe handling.

Dilute spill with water and wipe, or absorb with incombustible material such as sand or diatom earth, and collect in suitable

containers (e.g. stainless steel or plastic).

Use appropriate procedures to dispose the spilled material. See section 13.

7. Handling and storage

Handling

<General handling precautions>

Always wear proper protective equipment such as protective gloves and goggles/mask when handling. Avoid eye, skin, mucous membrane and clothing contact. Avoid breathing vapor or mist. Do not eat, drink or smoke in areas handling the product including storage, work areas. Keep away from all sources of ignition such as sparks, flame and heat. Wash thoroughly after handling.

<Ventilation>

Use only in a well-ventilated area equipped with local exhaust ventilation.

Users of this product must be properly trained for safety measures.

Storage

<Storage requirement>

Store and lock in cool dry, well-ventilated area protected from direct sunlight.

Store in original container or other suitable containers designed for liquid storage (e.g. stainless steel or polyethylene containers).

Keep container tightly closed and sealed to prevent leakage.

8. Exposure control /Personal protection

Engineering controls Use process enclosures or well-ventilated facilities with adequate general or local exhaust ventilation. Facilities storing or utilizing

this material should be equipped with an eyewash facility and a safety shower. Use antistatic device and explosion proof

equipment to prevent fire or explosion.

Concentration limits Not determined

Exposure limits TLV-TWA 1000ppm ACGIH(2005) (Ethanol)

Personal protective < Respiratory protection>

equipment Organic vapor respirators or positive pressure, self-contained breathing apparatus. Respirator selection must be based on

known or anticipated exposure levels.

<Protective Gloves>

Rubber gloves (e.g. butyl rubber, chloroprene rubber)

<Eye protection> Goggle <Skin protection>

Vinyl protective clothing, lab coat or antistatic protective clothing.

9. Physical and chemical properties

Physical state Liquid (particle suspension)
Color White (in suspension)

Odor(threshold) Alcohol
pH Not available
Melting Point Not available
Boiling Point Not available
Flash Point (closed cup)37.7
Evaporation Rate Not available
Flammability (Solid, gas) Not available

LEL/UEL (Upper)Not available (Lower)Not available

Vapor Pressure Not available
Vapor Density Not available
Specific Gravity (relative density) Not available

Solubility Not available /Easily suspended to water (hot/cold) and organic solvent (alcohol, etc.)

Partition Coefficient octanol/water Not available
Decomposition Temperature Not available
Autoignition temperature Not available
Viscosity Not available
Other data None

10. Stability and reactivity

Stability Stable at normal handling and storage conditions.

Hazardous polymerization Will not occur to produce hazardous substance at normal handling and storage conditions.

Conditions to Avoid Avoid all possible sources of ignition (sunlight, spark, flame, or heat).

Incompatibilities None

Hazardous Decomposition Will not occur at normal handling and storage conditions.

Products

11. Toxicological information

Acute Toxicity Data Ethanol Oral rat LD_{50} 13.7g/kg

Dermal Not available

Inhalation (vapor) rat LC_{50} 20,000ppm/10h (31,600ppm/4h) Inhalation (mist) rat LC_{50} 63,000ppm/4h (118mg/L)

Eye effects Ethanol OECD TG404 rabbit moderate

Draiz test rabbit moderately

Damage to comeal epithelium. Conjunctival hyperemia can take 1 or 2 days to heal. Severe irritation.

Prolonged and/or repeated skin contact may cause irritations and possibly dermatitis. Inhalation of high vapor concentrations may cause irritations to the respiratory system. In case of prolonged inhalation of high vapor

concentrations, narcotic effects may occur.

Respiratory/Skin effects No information available.

Ethanol

Germ cell mutagenicity Ethanol On rat and mouse, dominant lethality and aneuploidy induction in mice's germ cell have been reported.

Carcinogenicity Ethanol ACGIH: A4 (Not Classifiable as a Human Carcinogen)

Reproductive Effects Ethanol Chronic ingestion of large amounts of alcohol has been reported to cause teratogenic effects on unborn child

and other effects.

Single exposure Ethanol Oral ingestion in human may cause acute intoxication effects to central nervous system, and can be fatal.

Possible risks of irritation to respiratory tact, drowsiness, or dizziness have been reported.

Repeated exposure Ethanol Prolonged or repeated exposure can produce liver or nerve damage.

12. Ecological information

Ecotoxicity No information available.

Environmental No information available.

Physical No information available.

Other information The ecological effects of this product have not been evaluated. Avoid release to the environment.

13. Disposal considerations

Waste disposal Dispose in accordance with all applicable regulations. Dispose of its contents and waste via a licensed waste disposal contractor.

Contaminated containers Dispose in accordance with all applicable regulations. Dispose after cleaning up the containers and packaging until no residual of

and packaging contents can be observed. Use a licensed waste disposal contractor.

14. Transport information

regulations IMO : Not Regulated.

<Air Transport>
ICAO: Not Regulated.

IATA: Not Regulated.

Special safety practice Load the containers holding the product securely to prevent drop, fall or damage. Transport such containers carefully to prevent

significant wear or agitation. See Section 7. Handling and storage for reference when loading/unloading and transporting the

product.

15. Regulatory information

It was assumed that it was not a flammable liquid as a result of judging pertinent goods based on "United Nations Recommendations on the Transport of

 ${\bf Dangerous\ Goods''.\ However,\ take\ care\ on\ the\ handling,\ because\ this\ product\ contains\ 10-15\%\ ethanol.}$

The regulations that should be noted with the water containing a high concentration of ethanol are shown below.

US Federal TSCA /Ethanol: Listed on the TSCA inventory.

SARA Codes /Ethanol: acute, chronic, flammable.

State Ethanol can be found on the following state right to know lists: CA, NJ, PA, MN, MA

EU Risk phases: R10 flammable.

16. Other information

Reference

Notice to reader Disclaimer The information above is believed to be accurate and represents the best information currently available to us. It is provided in good

faith without warranty to assist in the proper handling and storage of this product. YMC Co., Ltd. makes no representations as to the accuracy or completeness of the information contained herein. Information is supplied on condition that persons receiving such information will make their own determination as to its suitability for their purposes prior to use. In no event will YMC Co., Ltd. be responsible for damages of any nature whatever resulting from the use of or reliance upon the information contained herein.

e Internal test result

ACGIH (1996), (2001) PATTY (5th, 2005) RTECS (2004) DFGOT (1996) HSDB (2005)

MSDS Revision Summary: MSDS Creation Date: July 8, 2009

Revision: 3